

Architectural LED

Linear Suspended

Metalux | Corelite | Neo-Ray

Good

Better


Best

Click on products to learn more



| | | WSL | Hugo | RZL | Jaylum | Iridium i3 | Continua CTA |
|------------------------|----------------------------------|----------------------|-----------------------------------|---------------------------------|--------------------|--------------------|------------------------------|
| APPLICABILITY | Education | ★★ | ★★★ | ★★ | ★★★ | ★★★ | ★★★ |
| | Office | ★★★ | ★★ | ★ | ★★★ | ★★ | ★★ |
| | Healthcare | ★★ | ★★ | ★★ | ★★ | ★★ | ★★ |
| | Retail | ★★★ | ★★★ | ★★★ | ★ | ★ | ★★ |
| FEATURES / PERFORMANCE | Construction | Cold Rolled Steel | Extruded Aluminum | Cold Rolled Steel | Cold Rolled Steel | Cold Rolled Steel | Extruded Aluminum |
| | Lengths | 4', 8', Cont. | 4', 8', 12', Cont. | 4', 8', 12', Cont. | 4', 8', Cont. | 4', 8', Cont. | 4', 8', 12', Cont. |
| | lm/W (Max) | 121 | 145 | 135 | 157 | 158 | 147 |
| | Lumens (Max) | 8000 (2000 lms/ft) | 8000 (2000 lms/ft) | 8800 (2200 lms/ft) | 8000 (2000 lms/ft) | 8000 (2000 lms/ft) | 6000 (1500 lms/ft) |
| | Up/Down % Options | 3 | 2 | 2 | 5 | 5 | 4+ |
| | CIE Type | Direct, Semi-Direct | Direct, Semi-Direct | Direct, Semi-Direct | Direct/Indirect | Direct/Indirect | Direct, Direct/Indirect |
| | Life (@60K) | L81 | L85 | L85 | L93 | L93 | L84 |
| | Shielding | WaveStream - Acrylic | Frost - Smooth, Drop Lens, Baffle | Frost -Linear Prismatic, Baffle | Frost - Smooth | Frost - Smooth | Frost - Continuous Roll Lens |
| | Companion Family Fixtures | Surface | Surface | Surface | Wall, Sconce | - | Wall |
| | Driver Location | Integral | Integral | Integral | Integral | Integral | Integral |
| | Emergency | Integrated | Integrated | Integrated | Integrated | Integrated | Integrated |
| | CRI | 80+ | 80+ / 90 | 80+ / 90 | 80+ / 90 | 80+ / 90 | 80+ / 90 |
| | Sensor Location | Integrated | Integrated, Side Mount | Integrated | Integrated | Integrated | Integrated, Side Mount |
| DLC | Standard | Premium | Premium | Premium | None | Premium | |
| VividTune™ | No | No | No | Tunable White | Tunable White | No | |
| INTEGRATED CONTROLS | Stand Alone Daylight / Occupancy | ✓ | | ✓ | ✓ | ✓ | |
| | WaveLinx | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | Enlighted | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | DLVP | ✓ | | | | | |

Notes: 1. ★★★ = high applicability, ★★ = medium applicability, ★ = low applicability, blank = non-applicable



| | | Continua S04 | Iridium i2 WaveStream | Divide | Vaulta | Discreet | Cirque |
|------------------------|----------------------------------|-------------------------------|--------------------------|--|---|---|---|
| APPLICABILITY | Education | ★★★ | ★★★ | ★★ | ★★ | ★★ | ★★ |
| | Office | ★★★ | ★★ | ★★★ | ★★★ | ★★★ | ★★★ |
| | Healthcare | ★★ | ★★ | ★ | ★★ | ★★ | ★★ |
| | Retail | ★★ | ★ | ★★ | ★★ | ★★ | ★ |
| FEATURES / PERFORMANCE | Construction | Extruded Aluminum | Cold Rolled Steel | Extruded Aluminum | Extruded Aluminum | Extruded Aluminum | Extruded Aluminum |
| | Lengths | 4', 6', 8', 12', Cont. | 4', 8', Cont. | 4', 8', Cont. | 4', 6', 8', 12' Cont. | 4', 6', 8', 12' Cont. | 4', 6', 8', 12' Cont. |
| | lm/W (Max) | 135 | 114 | 140 | 127 | 127 | 164 |
| | Lumens (Max) | 10,800 lm (2,700 lms/ft) | 7200 (1800 lms/ft) | 6000 (1500 lms/ft) | 1250 (1500 lms/ft) | 11920 (2980 lms/ft) | 1500 (2475 lms/ft) |
| | Up/Down % Options | 20+ | 3 | 2 | 28+ | 28+ | 28+ |
| | CIE Type | Direct, Direct/Indirect | Direct, Direct/Indirect | Direct, Direct/Indirect | Direct, Direct/Indirect | Direct, Direct/Indirect | Direct, Direct/Indirect, Indirect |
| | Life (@60K) | L84 | L81 | L87 | L85 | L85 | L90 |
| | Shielding | Frost - Continuous Roll Lens | Frost - Linear Prismatic | WaveStream - Acrylic Specular, Diffuse | Discrete Optics, Black or White Baffles | Discrete Optics, Black or White Baffles | Discrete Optics, Black or White Baffles |
| | Companion Family Fixtures | Recessed | - | Surface, Wall, Recessed | Surface | Surface | Surface |
| | Driver Location | Integral | Integral | Integral | Integral | Integral | Integral |
| | Emergency | Integrated | Integrated | Integrated | Integrated | Integrated | Integrated |
| | CRI | 80+ / 90 | 80+ / 90 | 80+ / 90 | 80+ / 90 | 90+ | 80+ / 90 |
| | Sensor Location | Integrated, Endcap/Side Mount | Integrated | Integrated | Integrated | Integrated | Integrated |
| DLC | Premium | Standard | Premium | In-process | In-process | In-process | |
| VividTune™ | No | No | No | No | No | No | |
| INTEGRATED CONTROLS | Stand Alone Daylight / Occupancy | | ✓ | | | | |
| | WaveLinx | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | Enlighted | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | DLVP | | | | | | |

Notes: 1. ★★★ = high applicability, ★★ = medium applicability, ★ = low applicability, blank = non-applicable

Architectural LED

Linear Suspended

Best

Click on products to learn more



| | | Omni | Define | Converge | Covera |
|----------------------------|----------------------------------|---|---|------------------------------|--------------------|
| APPLICABILITY ¹ | Education | ★★ | ★★ | ★★★ | ★★★ |
| | Office | ★★★ | ★★★ | ★★★ | ★★★ |
| | Healthcare | ★★ | ★★ | ★ | ★ |
| | Retail | ★ | ★ | ★★ | ★★ |
| FEATURES / PERFORMANCE | Construction | Extruded Aluminum | Extruded Aluminum | Extruded Aluminum | Metal cast |
| | Lengths | 4', 6', 8', 12' Cont. | 2' - 12', Cont. | 4', 8', Cont. | 2', 4' |
| | lm/W (Max) | 121 | 164 | 119 | 157 |
| | Lumens (Max) | 1500 (2475 lms/ft) | 9900 (2475 lms/ft) | 6700 (1700 lms/ft) | 8000 (2000 lms/ft) |
| | Up/Down % Options | 28+ | ∞ | 3 | 2 |
| | CIE Type | Direct, Direct/Indirect, Indirect | Direct, Direct/Indirect, Indirect | Direct, Direct/Indirect | Direct/Indirect |
| | Life (@60K) | L90 | L90 | L85 | L93 |
| | Shielding | Discrete Optics, Black or White Baffles | Frost - Smooth, Drop & Regressed, Asymmetric and Batwing Lens | WaveStream - Acrylic Diffuse | Frost - Smooth |
| | Companion Family Fixtures | Surface | Surface, Wall, Recessed, Perimeter | - | - |
| | Driver Location | Integral | Integral | Remote w/ Luxwire | Integral |
| | Emergency | Integrated | Integrated | Remote | Integrated |
| | CRI | 80+ / 90 | 80+ / 90 | 80+ / 90 | 80+ / 90 |
| | Sensor Location | Integrated | Integrated | Tile Mount | Integrated |
| DLC | In-Process | Premium | None | None | |
| VividTune™ | No | Tunable White | No | No | |
| INTEGRATED CONTROLS | Stand Alone Daylight / Occupancy | | ✓ | ✓ | ✓ |
| | WaveLinx | ✓ | ✓ | ✓ | ✓ |
| | Enlighted | ✓ | ✓ | ✓ | ✓ |
| | DLVP | | | ✓ | |

Notes: 1. ★★★ = high applicability, ★★ = medium applicability, ★ = low applicability, blank = non-applicable



Cooper Lighting Solutions
1121 Highway 74 South
Peachtree City, GA 30269
P: 770-486-4800
www.cooperlighting.com

Canada Sales
5925 McLaughlin Road
Mississauga, Ontario L5R 1B8
P: 905-501-3000
F: 905-501-3172

© 2023 Cooper Lighting Solutions
All Rights Reserved
Publication No. SA524005EN-web
July 30, 2023 5:35 PM

Cooper Lighting Solutions is a registered trademark.
All other trademarks are property of their respective owners.
Product availability, specifications, and compliances are subject to change without notice.