Architectural LED
Recessed

Corelite

Good ———————— **Better** ———————— **Best**

Click on products to learn more

		Perceive PT	Class RX/ZX	Class D3X-LP	Perceive PD	InDepth	Bridge	Class R2X	Divide
APPLICABILITY	Education	★★★	★★★	★★	★★★	★★★	★★	★★★	★★
	Office	★★★	★★★	★★★	★★★	★★★	★★★	★★★	★★★
	Healthcare	★★★	★	★★	★★★	★★	★	★★★	★★★
	Retail	★★	★★	★★	★★	★★	★★	★★	★
FEATURES / PERFORMANCE	Sizes	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4, 4x4	1x4, 2x2, 2x4, Metric	1x4, 2x2, 2x4, Metric	1x4, 2x2, 2x4
	Housing Depth	2 1/4" 3 3/4" w/ battery	3 1/4"	3 1/4" (2x2, 2x4) 5 11/16" (1x4)	3 1/4"	4 5/16"	3 7/8"	2 7/8"	2 1/4"
	lm/W (Max)	137	145	139	137	127	118	134	137
	Lumens (Max)	9000	7600	7800	9000	9000	7300	8000	7500
	Life (@60K)	L85	L94	L93	L85	L84	L80	L87	L87
	Lens	Acrylic (3D Perceive Optics)	Round (R), Flat (Z) Frost - Smooth	Frost - Smooth, Perf Inlays	Acrylic (3D Perceive Optics)	1", 2" Cube Regress; 1", 2", 3" Cube Drop; 2" Single & Double Curve Regress & Drop; Sweep Regress & Drop	Acrylic (Wavestream), Perf Inlays	Round (R), Frost - Smooth	Acrylic (Wavestream), Specular, Diffuse
	Emergency	Integrated	Integrated	Integrated	Integrated	Integrated, Indicator is Remote	Integrated	Integrated	Integrated
	CRI	80+ / 90	80+ / 90	80+ / 90	80+ / 90	80+	80+ / 90	80+ / 90	80+ / 90
	Sensor Location	Integrated	Integrated	Integrated	Integrated	Tile Mount	Integrated	Tile Mount	Integrated
	DLC	Premium	Standard	Standard	Premium	Premium	Standard	Standard	Premium
	Air Return	No	Yes	No	No	No	Yes, concealed	Yes	No
	VividTune™	Yes	Tunable White	Tunable White	No	No	No	No	No
INTEGRATED CONTROLS	WaveLinx Lite	✔	✔	✔	✔	✔	✔		
	WaveLinx Pro	✔	✔	✔	✔	✔	✔		✔
	WaveLinx, No Sensor	✔	✔	✔	✔	✔			
	Enlighted	✔	✔	✔	✔	✔	✔	✔	✔
	DLVP		✔		✔	✔	✔		
	BioUp		✔						

Notes: 1. ★★★ = high applicability, ★★ = medium applicability, ★ = low applicability, blank = non-applicable

COOPER
Lighting Solutions